

EKDS16124-316

STAINLESS STEEL COMPACT VERSION, DOUBLE DOOR ENCLOSURE



IP 55, NEMA 12, 13, IK 10

D	400
H	1600
W	1200
	135.7
h	1494
w	1094
Part No.	EKDS16124-316

Material: AISI 304L pre-grained stainless steel / AISI 316L. Body and removable rear panel: 1.5 mm. Door: 2 mm. Bottom Plates: 1.5 mm.

Body: One piece enclosure body. Integrated depth profiles with hole pattern allowing mounting plate adjustable in depth.

Door: Mounted with four hinges. Including door frame with 25 mm hole pattern.

Rear panel: Fitted by M6 torx screws. Standard facilities for rear door mounting. Split rear panels in 1600 mm wide enclosures.

Lock: External espagnolette 4-point locking system. Standard fitted double-bit 3 mm insert. It can be exchanged for standard range of inserts, Euro-cylinder and swing handle.

Bottom plates: One piece bottom plate with injected polyurethane gasket to ensure maximum sealing.

Earthing: Door is equipped with separate welded earthing studs and earthing to the frame can be accomplished by using the ECF.

Mounting plate: Double folded and slides into position. Adjustable in depth by steps of 25 mm. Mounting plate is delivered attached on the outside of the enclosure packaging. Fitted inside for 1600 mm wide enclosures. For 1600 mm wide, filler plate is included.

Finish: 240s pre-grained stainless steel (0.5 microns average).

Protection: Double door version, complies with IP 55, NEMA 12 and 13, IK 10. Individual doors with welded vertical divider, complies with IP 66, NEMA 4X, 12 and 13, IK 10.

Delivery: One piece body with fitted door, bottom plates and mounting plate, including door earthing studs. Delivered on a pallet with width identical to the enclosure to allow installing of equipment without removal. Mounting plate is attached to the outside of the enclosure packaging. All the packing material is recyclable.