

SITOP PSU8200 24 V/20 A  
 SITOP PSU8200 20A STABILIZED POWER SUPPLY INPUT: 120-230 V AC 110-220 V DC OUTPUT: 24 V/20 A DC



| Input                                     |  |
|---|--|
| Input                                     | 1-phase AC or DC   |
| Supply voltage                            |  |
| • at DC                                   | 110 ... 220 V  |
| Rated voltage value $V_{in}$ rated        | 120 ... 230 V  |
| Voltage range AC                          | 85 ... 275 V   |
| • Note                                    | Derating of temperature necessary down to 50 °C at $V_{in} < 100$ V AC or DC |
| Input voltage                             |  |
| • at DC                                   | 88 ... 350 V   |
| Wide-range input                          | Yes  |
| Mains buffering at $I_{out}$ rated, min.  | 20 ms; at $V_{in} = 230$ V   |
| Rated line frequency 1                    | 50 Hz  |
| Rated line frequency 2                    | 60 Hz  |
| Rated line range                          | 45 ... 65 Hz   |
| Input current                             |  |
| • at rated input voltage 120 V            | 4.6 A  |
| • at rated input voltage 230 V            | 2.5 A  |
| Switch-on current limiting (+25 °C), max. | 20 A   |

|   |  |
|---|--|
| I <sup>2</sup> t, max.                        | 5 A <sup>2</sup> ·s  |
| Built-in incoming fuse                        | Yes  |
| Protection in the mains power input (IEC 898) | Recommended miniature circuit breaker at 1-phase operation: 10 A characteristic C; required at 2-phase operation: circuit breaker 2-pole connected or circuit breaker 3RV2711-1HD10 (UL 489) at 120 V or 3RV2711-1ED10 (UL 489) at 230 V |

## Output

|   |   |
|---|---|
| Output  | Controlled, isolated DC voltage                                 |
| Rated voltage V <sub>out</sub> DC                             | 24 V  |
| Total tolerance, static ±                                     | 3 %   |
| Static mains compensation, approx.                            | 0.1 %   |
| Static load balancing, approx.                                | 0.3 %   |
| Residual ripple peak-peak, max.                               | 100 mV  |
| Residual ripple peak-peak, typ.                               | 80 mV   |
| Spikes peak-peak, max. (bandwidth: 20 MHz)                    | 200 mV  |
| Spikes peak-peak, typ. (bandwidth: 20 MHz)                    | 100 mV  |
| Adjustment range  | 24 ... 28.8 V   |
| Product function Output voltage adjustable                    | Yes   |
| Output voltage setting  | via potentiometer   |
| Status display  | Green LED for 24 V OK   |
| Signaling   | Relay contact (NO contact, rating 60 V DC/ 0.3 A) for "24 V OK" |
| On/off behavior   | No overshoot of V <sub>out</sub> (soft start)                   |
| Startup delay, max.   | 0.25 s  |
| Voltage rise, typ.  | 50 ms   |
| Rated current value I <sub>out</sub> rated                    | 20 A  |
| Current range   | 0 ... 20 A  |
| • Note  | +60 ... +70 °C: Derating 3%/K                                   |
| Supplied active power typical                                 | 480 W   |
| Short-term overload current                                   |   |
| • at short-circuit during operation typical                   | 60 A  |
| Duration of overloading capability for excess current         |   |
| • at short-circuit during operation                           | 25 ms   |
| Constant overload current                                     |   |
| • on short-circuiting during the start-up typical             | 30 A  |
| Parallel switching for enhanced performance                   | Yes; switchable characteristic                                  |
| Numbers of parallel switchable units for enhanced performance | 2   |

## Efficiency

|   |      |
|---|------|
| Efficiency at V <sub>out</sub> rated, I <sub>out</sub> rated, approx. | 93 % |
| Power loss at V <sub>out</sub> rated, I <sub>out</sub> rated, approx. | 42 W |

## Closed-loop control

|  |       |
|--|-------|
| Dynamic mains compensation (V <sub>in</sub> rated ±15 %), max. | 0.5 % |
|--|-------|

|  |      |
|--|------|
| Dynamic load smoothing (I <sub>out</sub> : 50/100/50 %), U <sub>out</sub> ± typ. | 1 %  |
| Load step setting time 50 to 100%, typ.  | 1 ms |
| Load step setting time 100 to 50%, typ.  | 1 ms |
| Setting time maximum   | 5 ms |

### Protection and monitoring

|  |  |
|--|--|
| Output overvoltage protection  | < 33 V   |
| Current limitation, typ.   | 21.5 A   |
| Property of the output Short-circuit proof   | Yes  |
| Short-circuit protection   | Alternatively, constant current characteristic approx. 23 A or latching shutdown |
| Enduring short circuit current RMS value <ul style="list-style-type: none"> <li>• typical</li> </ul> | 23 A   |
| Overcurrent overload capability in normal operation  | overload capability 150 % I <sub>out</sub> rated up to 5 s/min                   |
| Overload/short-circuit indicator   | LED yellow for "overload", LED red for "latching shutdown"                       |

### Safety

|  |   |
|--|---|
| Primary/secondary isolation  | Yes   |
| Galvanic isolation   | Safety extra-low output voltage U <sub>out</sub> acc. to EN 60950-1 and EN 50178  |
| Protection class   | Class I   |
| Leakage current <ul style="list-style-type: none"> <li>• maximum</li> <li>• typical</li> </ul> | 3.5 mA<br>1 mA  |
| CE mark  | Yes   |
| UL/cUL (CSA) approval  | cULus-Listed (UL 508, CSA C22.2 No. 107.1), File E197259  |
| Explosion protection   | IECEX Ex nA nC IIC T3 Gc; ATEX (EX) II 3G Ex nA nC IIC T3 Gc; cCSAus (CSA C22.2 No. 213, ANSI/ISA-12.12.01) Class I, Div. 2, Group ABCD, T3 |
| FM approval  | -   |
| CB approval  | No  |
| Marine approval  | GL, ABS   |
| Degree of protection (EN 60529)  | IP20  |

### EMC

|                             |                  |
|-----------------------------|------------------|
| Emitted interference        | EN 55022 Class B |
| Supply harmonics limitation | EN 61000-3-2     |
| Noise immunity              | EN 61000-6-2     |

### Operating data

|  |   |
|--|---|
| Ambient temperature <ul style="list-style-type: none"> <li>• during operation</li> <li>— Note</li> <li>• during transport</li> <li>• during storage</li> </ul> | -25 ... +70 °C<br>with natural convection<br>-40 ... +85 °C<br>-40 ... +85 °C |
|--|---|

|                                      |                                    |
|--------------------------------------|------------------------------------|
| Humidity class according to EN 60721 | Climate class 3K3, no condensation |
|--------------------------------------|------------------------------------|

| Mechanics   |  |
|---|--|
| Connection technology   | screw-type terminals   |
| Connections   |  |
| <ul style="list-style-type: none"> <li>• Supply input</li> <li>• Output</li> <li>• Auxiliary</li> </ul> | L, N, PE: 1 screw terminal each for 0.2 ... 4 mm <sup>2</sup> single-core/finely stranded<br>+, -: 2 screw terminals each for 0.2 ... 4 mm <sup>2</sup><br>13, 14 (alarm signal): 1 screw terminal each for 0.14 ... 1.5 mm <sup>2</sup> |
| Width of the enclosure  | 90 mm  |
| Height of the enclosure   | 125 mm   |
| Depth of the enclosure  | 125 mm   |
| Weight, approx.   | 1.2 kg   |
| Product feature of the enclosure housing for side-by-side mounting                                      | Yes  |
| Installation  | Snaps onto DIN rail EN 60715 35x7.5/15   |
| Electrical accessories  | Buffer module  |
| Mechanical accessories  | Device identification label 20 mm × 7 mm, pale turquoise<br>3RT1900-1SB20  |
| MTBF at 40 °C   | 667 048 h  |
| Other information   | Specifications at rated input voltage and ambient temperature +25 °C (unless otherwise specified)  |