



SITOP PSU300M 48 V/10 A  
 SITOP PSU300M 48V/10A STABILIZED POWER SUPPLY INPUT:  
 400-500 V 3 AC OUTPUT: 48 V/10 A DC

Input	
Input	3-phase AC
Rated voltage value $V_{in}$ rated	400 ... 500 V
Voltage range AC	320 ... 575 V
Wide-range input	Yes
Overvoltage resistance	$2.3 \times V_{in}$ rated, 1.3 ms
Mains buffering at $I_{out}$ rated, min.	15 ms; at $V_{in} = 400$ V
Rated line frequency	50 ... 60 Hz
Rated line range	47 ... 63 Hz
Input current	
• at rated input voltage 400 V	1.2 A
• at rated input voltage 500 V	1 A
Switch-on current limiting (+25 °C), max.	18 A
$I^2t$ , max.	0.8 A <sup>2</sup> ·s
Built-in incoming fuse	none
Protection in the mains power input (IEC 898)	Required: 3-pole connected miniature circuit breaker 6 ... 16 A characteristic C or circuit breaker 3RV2011-1DA10 (setting 3 A) or 3RV2711-1DD10 (UL 489)

Output	
Output	Controlled, isolated DC voltage
Rated voltage $V_{out}$ DC	48 V
Total tolerance, static $\pm$	3 %
Static mains compensation, approx.	0.1 %
Static load balancing, approx.	0.2 %
Residual ripple peak-peak, max.	100 mV

Spikes peak-peak, max. (bandwidth: 20 MHz)	200 mV
Adjustment range	42 ... 56 V
Product function Output voltage adjustable	Yes
Output voltage setting	via potentiometer; max. 480 W
Status display	Green LED for 48 V OK
Signaling	Relay contact (NO contact, rating 60 V DC/ 0.3 A) for 48 V OK
On/off behavior	No overshoot of Vout (soft start)
Startup delay, max.	2.5 s
Voltage rise, typ.	150 ms
Voltage increase time of the output voltage maximum	500 ms
Rated current value Iout rated	10 A
Current range	0 ... 10 A
• Note	+60 ... +70 °C: Derating 3%/K
Active power supplied typical	480 W
Short-term overload current	
• at short-circuit during operation typical	23 A
Duration of overloading capability for excess current	
• at short-circuit during operation	25 ms
Constant overload current	
• on short-circuiting during the start-up typical	11 A
Parallel switching for enhanced performance	Yes; switchable characteristic
Numbers of parallel switchable units for enhanced performance	2

#### Efficiency

Efficiency at Vout rated, Iout rated, approx.	93 %
Power loss at Vout rated, Iout rated, approx.	36 W

#### Closed-loop control

Dynamic mains compensation (Vin rated $\pm 15\%$ ), max.	1 %
Dynamic load smoothing (Iout: 50/100/50 %), Uout $\pm$ typ.	2 %
Load step setting time 50 to 100%, typ.	2 ms
Load step setting time 100 to 50%, typ.	2 ms
Setting time maximum	10 ms

#### Protection and monitoring

Output overvoltage protection	Yes, according to EN 60950-1
Current limitation, typ.	11 A
Property of the output Short-circuit proof	Yes
Short-circuit protection	Alternatively, constant current characteristic approx. 11 A or latching shutdown
Enduring short circuit current RMS value	
• typical	11 A

Overcurrent overload capability in normal operation	overload capability 150 % I <sub>out</sub> rated up to 5 s/min
Overload/short-circuit indicator	LED yellow for "overload", LED red for "latching shutdown"

### Safety

Primary/secondary isolation	Yes
Galvanic isolation	Safety extra-low output voltage U <sub>out</sub> acc. to EN 60950-1 and EN 50178
Protection class	Class I
Leakage current <ul style="list-style-type: none"> <li>• maximum</li> </ul>	3.5 mA
CE mark	Yes
UL/CSA approval	Yes
UL/cUL (CSA) approval	cULus-Listed (UL 508, CSA C22.2 No. 107.1), File E197259
Explosion protection	IECEx Ex nA nC IIC T4 Gc; ATEX (EX) II 3G Ex nA nC IIC T4; cCSAus (CSA C22.2 No. 213, ANSI/ISA-12.12.01) Class I, Div. 2, Group ABCD, T4
Certificate of suitability IECEx	No
Certificate of suitability NEC Class 2	No
FM approval	-
CB approval	Yes
Marine approval	GL, ABS
Degree of protection (EN 60529)	IP20

### EMC

Emitted interference	EN 55022 Class B
Supply harmonics limitation	EN 61000-3-2
Noise immunity	EN 61000-6-2

### Operating data

Ambient temperature <ul style="list-style-type: none"> <li>• during operation</li> <li>— Note</li> <li>• during transport</li> <li>• during storage</li> </ul>	-10 ... +70 °C with natural convection -40 ... +85 °C -40 ... +85 °C
Humidity class according to EN 60721	Climate class 3K3, no condensation

### Mechanics

Connection technology	screw-type terminals
Connections <ul style="list-style-type: none"> <li>• Supply input</li> <li>• Output</li> <li>• Auxiliary</li> </ul>	L1, L2, L3, PE: 1 screw terminal each for 0.5 ... 2.5 mm <sup>2</sup> single-core/finely stranded +, -: 2 screw terminals each for 0.2 ... 4 mm <sup>2</sup> 13, 14 (alarm signal): 1 screw terminal each for 0.14 ... 1.5 mm <sup>2</sup>
Width of the enclosure	70 mm
Height of the enclosure	125 mm
Depth of the enclosure	125 mm

Weight, approx.	1.2 kg
Product property of the enclosure housing for side-by-side mounting	Yes
Installation	Snaps onto DIN rail EN 60715 35x7.5/15
Mechanical accessories	Device identification label 20 mm × 7 mm, pastel-turquoise 3RT1900-1SB20
Other information	Specifications at rated input voltage and ambient temperature +25 °C (unless otherwise specified)