

flexible copper busbar, plain, insulated (01 184)

Description

Article

Part No.: 01 184

flexible copper busbar, plain, insulated

727 A, length 2 m

10 x 24 x 1

System

60Classic

Product group 06

Subgroup 81

pack size 1

EAN 4021267011840

Advantages of the product

The laminated Cu busbars considerably reduce the effort of connecting busbars. The bending devices required for solid copper busbars are unnecessary. The 2mm-thick insulation means that no additional covering is required.

Catalog page 2015 : 7/7

eCl@ss 6.1 27370303

eCl@ss 7.1 27370303

ETIM 4.0 EC001522

ETIM 5.0 EC001522

Approvals

Standards

IEC 61439-1:2011

Approvals

UL, Germanischer Lloyd



for UL feeder circuits >250V

Type number: 10x24x1

UL file: E197039, UL category (for USA): QEUY2 <http://www.ul.com>

UL file: E197039, UL category (for Canada): QEUY8 <http://www.ul.com>

CCC approval: no certification required

Product data

Electrical data

Rated current (IEC): 727 A

Power dissipation:

The power dissipation at a typical load of 80% of the rated current results to 59.4 W.

(The power dissipation for operation with rated current would be 92.8 W.)

short-circuit withstandability: see product description of the used busbar support

the current carrying capacity as a function of temperature can be calculated in the section "Technics"

Mechanical data

L x W x D: 2000 x 28 x 14

Weight: 450 kg/100

cross-section: 240 mm²

10-layer, 24 x 1mm, 2m long

Material properties

Insulation: temperature withstand up to 105 °C

self-extinguishing, V0 according to UL 94


breakdown voltage 20 kV

stretching 370 %

Accessories



01 303
holder for flexible copper



01 298
holder for flexible copper
for 1x lam. Cu of 6 x 15.5 x 0.8 to 10 x 63 x 1