

universal busbar support (01 495)



Description

Article

Part No.: 01 495

universal busbar support

3-pole with internal screw holes

for busbars 12, 15, 20, 25, 30 x 5, 10

System

60Classic

Product group 06

Subgroup 09

pack size 10

EAN 4021267014957

Advantages of the product

With internal screw holes

can also be used as centre support

Catalog page 2015 : 2/1

eCl@ss 6.1 27400607
eCl@ss 7.1 27400607
ETIM 4.0 EC001166
ETIM 5.0 EC001166

Approvals

Standards

IEC 61439-1:2011

Approvals

Germanischer Lloyd



Type number: S610

CCC approval: no certification required

Product data

Electrical data

Rated voltage (IEC) AC: 690 V

Power dissipation:

The power dissipation at a typical load of 80% of the rated current results to 0 W.
(The power dissipation for operation with rated current would be 0 W.)

Rated surge voltage U_{imp} : 8 kV
max. permitted voltage (IEC) AC: 1000 V
max. permitted voltage (IEC) DC: 1500 V

short-circuit capacity IEC / EN :

I_{pk} = min. 31kA (2 busbar supports in 580mm distance)

go to calculation for [3-pole system \(IEC\)](#)

Mechanical data

W x H x D: 20 x 191 x 50

Weight: 12.7 kg/100

Poles: 3-pole

for busbars: 12, 15, 20, 25, 30 x 5, 10

Material properties

Main temperature stability 125°C,

body: self-extinguishing in acc. to UL 94,

creepage resistance CTI 200,


halogen-free

Screws: screw +/- (PZ2), galvanized, chromized

Reference

Torque for the screws of the busbar support $M_d = 4\text{Nm}$

Accessories



01 573

end cover

for busbar supports 01 495, 01 500, 01 508 and 01 484