

universal busbar support (01 500)



Description

Article

Part No.: 01 500

universal busbar support

3-pole with additional external screw holes

for busbars 12, 15, 20, 25, 30 x 5, 10

System

60Classic

Product group 06

Subgroup 09

pack size 10

EAN 4021267015008

Advantages of the product

With additional external screw holes

can also be used as centre support

Catalog page 2015 : 2/1

eCl@ss 6.1 27400607
eCl@ss 7.1 27400607
ETIM 4.0 EC001166
ETIM 5.0 EC001166

Approvals

Standards

IEC 61439-1:2011

Approvals

Germanischer Lloyd



Type number: S610

CCC approval: no certification required

Product data

Electrical data

Rated voltage (IEC) AC: 690 V

Power dissipation:

The power dissipation at a typical load of 80% of the rated current results to 0 W.
(The power dissipation for operation with rated current would be 0 W.)

Rated surge voltage U_{imp} : 8 kV
max. permitted voltage (IEC) AC: 1000 V
max. permitted voltage (IEC) DC: 1500 V

short-circuit capacity IEC / EN :

I_{pk} = min. 31kA (2 busbar supports in 580mm distance)

go to calculation for [3-pole system \(IEC\)](#)

Mechanical data

W x H x D: 20 x 215 x 50

Weight: 13.7 kg/100

Poles: 3-pole

for busbars: 12, 15, 20, 25, 30 x 5, 10

Material properties

Main temperature stability 125°C,


body: self-extinguishing in acc. to UL 94,

creepage resistance CTI 200,

halogen-free

Screws: screw +/- (PZ2), galvanized, chromized

Accessories



01 573

end cover

for busbar supports 01 495, 01 500, 01 508 and 01 484