

NH fuse switch-discon. size 1, 250 A, panel mounting (33 393)



Description

Article

Part No.: 33 393

QUADRON® Panel

NH fuse switch-discon. size 1, 250 A, panel mounting

connection box terminal

System

Mounting plate

Product group 09

Subgroup 06

pack size 1

EAN 4021267333935

Advantages of the product

For safe connection of the leads, the shock protection is split into 2.

Self-closing inspection holes are available in the cover.

eCl@ss 6.1 27142108
eCl@ss 7.1 27142108
ETIM 4.0 EC001040
ETIM 5.0 EC001040

Approvals

Standards

IEC 60947-1:2007 + A1:2010 + A2:2014
IEC 60947-3:2008 + A1:2012

Approvals

IEC (CB)



Type number: QCB-NH1

Product data

Electrical data

Rated current (IEC): 250 A
Rated voltage (IEC) AC: 690 V
Rated voltage (IEC) DC: 440 V

Utilisation category AC-22B (400V)
AC (IEC 60947-3) : AC-23B (400V/160A)
AC-21B (690V)
AC-20B (1000V) at pollution degree 2

visible information required if used at more than 690V AC: do not switch under load

Utilisation category DC specifications: 2 current paths (L1,L3) in series
DC (IEC 60947-3) : DC-20B (440V)
DC-20B (1000V) at pollution degree 2

visible information required if used at more than 440V DC: do not switch under load

Power dissipation:

The power dissipation at a typical load of 80% of the rated current results to 9 W.
(The power dissipation for operation with rated current would be 14.1 W.)

rated isolation voltage U_i (AC): 800 V

Rated surge voltage U_{imp} : 6 kV

max. permitted voltage (IEC) AC: 800 V

max. permitted voltage (IEC) DC: 800 V

rated peak withstand current I_{pk} : 13.7 kA

cond. rated short-circuit current with fuses: 80 kA / 690 V

approved with fuse links of characteristics: gG

rated short-time withstand current I_{CW} : 8,1kA / 1s

for fuse links IEC 60269-2-1 (I) / DIN VDE 0636-201 size 1 up to 23W power dissipation

Entsprechend den angegebenen AC- und DC- Schalteigenschaften und unter Berücksichtigung der Überlastbedingungen, sind gewisse Abstände zu geerdeten Metallteilen einzuhalten. Nähere Informationen auf Anfrage.

Bei Verwendung als Trennschalter ist die Einhaltung der Abstände nicht erforderlich.

Degree of protection IP30 at front, degree of protection near terminal depends on installation

Mechanical data

W x H x D: 184 x 243 x 112

Weight: 191 kg/100

Poles: 3-pole

front degree of protection: IP30

Terminal points

box terminal

Cu 70-185mm²f

Cu 35-150mm²s(r)

Cu 35-120mm²f+AE

la.Cu 15.5-24mm large

terminal space 24.5 x 12mm

min. terminal space height 3mm

(flexible cables of maximum cross-section may not fit when using wire-end ferrule)

Material properties

| | |
|-------------------------|--|
| Main body: | temperature stability 125°C, self-extinguishing in acc. to UL 94, creepage resistance CTI 200, halogen-free |
| Shock protection cover: | temperature stability 125°C, self-extinguishing in acc. to UL 94, creepage resistance CTI 200 |
| Handle: | temperature stability 125°C, self-extinguishing in acc. to UL 94, creepage resistance CTI 200, halogen-free |
| Contacts: | spring-loaded copper contacts, silver plated |


Version

Variant with M10 connection screws: 33 201

Variant with electromechanical fuse monitoring: 33 149

Variant with electronic fuse monitoring: 33 330


Accessories




33 142
cover for cable lugs
for NH fuse switch disconnecter size 1



33 145
prism terminal, double
2x 35-70 mm²
size 1




33 152
Trim frame
215 x 330
size 1




33 155
barrier for handle
for fuse switch-disconnector size 1-3




33 157
lid interlock
for sealing wire and padlocks
Size 1 - 3




33 158
rapid mounting set
rails centre distance 125 mm or 150 mm
size 1 - 2




33 163
clamp-type connection
70-150 mm²
size 1



33 166
prism terminal for fuse switch-disconnector
35-150mm², Cu and Al
size 1



33 917
pilot switch for lid position
pilot switch: 1 reversing switch: 250V AC / 5A; 30V DC / 4A
Size 1



33 918
arcing chamber
QCB-NH1